



HOT MAX-M

HMB HOT AC 110

Mibrasa oven with heated holding drawers and top heated cupboard



TECHNICAL INFORMATION

Item	HMB HOT AC 110
Fire up time ¹	45 min
Cooking temperature	482-662 °F / 250-350 °C
Initial charcoal load ¹	33 lb / 15 kg
Production*	220.5 lb/h / 100 kg/h
Charcoal load duration ²	8 h
Equivalent power*	6.7 hp / 5 kW
Exhaust rate	1883 cfm / 3200 m ³ /h
Net weight ³	1669 lb / 757 kg
Crated weight	1978 lb / 897 kg
Crate dimensions (WxDxH)	1) 43.3 x 43.3 x 53.2 in / 1100 x 1100 x 1350 mm 2) 43.3 x 43.3 x 80.7 in / 1100 x 1100 x 2050 mm

*Approximate data

1. Consult instruction manual

2. Will vary depending on quality of charcoal

3. Weight with accessories included

FEATURES

OUR CHARCOAL OVENS WITH **hot** HEATED HOLDING DRAWERS

The Mibrasa® oven is a closed grill designed and engineered in our workshops. Made from the best quality steel by expert hands, our grills are designed to satisfy even the most demanding chefs.


The technical specifications allow the user to accurately control the air flow through the grill, changing the intensity of the embers. This is an extremely efficient way of cooking and cuts down the amount of charcoal needed.

With the HOT series take full control by optimizing the residual-heat from the Mibrasa® oven to hold ingredients in three temperature zones on the unit. The seamless lineal design makes the Mibrasa® HOT the most comprehensive charcoal oven station for any chef that prioritizes an effective and cost-efficient kitchen.

PAX PER SERVICE*



GRILL DIMENSIONS



INCLUDED ACCESSORIES

- Grill [2] [GT110]
- Mibrasa tongs [TG]
- Ash shovel [PALA]
- Firebreak-dissipating filter [FB-DF]
- Ember poker [PK110]
- Grill brush [CEP]
- Heating rack top cabinet [SBAC] Gastronorms
- [1x GN1/2, 1x GN1/1]


RECOMMENDED ACCESSORIES

- Castors [WINOX]
- Removable grease collector [REG3/4]
- Consult catalogue for kitchenware and grillware


QUALITY GUARANTEE




Front view




Side view



Option 1



Option 2



CUSTOMIZE

DOOR COLOR



BLACK



RED



YELLOW



STAINLESS STEEL



BLUE

EDITION



GOLD



BLACK



COPPER



TITANIUM



SILVER



WOOD*

The Edition finishes are applied to the logos, door handle and the thermometer casing.

*Only on the door handle (logos and thermometer casing in silver)

INSTALLATION GUIDELINES AND SAFETY STANDARDS

Clearances to construction / other appliances from oven	3 in / 76 mm
Clearances of flammable materials from oven	12 in / 300 mm
Clearance of workspace from front of the oven	44 in / 1100 mm




It is recommended to use a lifting device to lift the oven and place on the countertop/cabinet. Consult oven instruction manual for further information.

Specifications and design are subject to change without notice.


GASTRONORM CAPACITY

HOT DRAWER (x3)



Residual temperatures of the drawers between 131 °F / 55 °C and 194 °F / 90 °C based on oven working at 572 °F / 300 °C.
Maximum gastronorm height 2.36 in / 6 cm.

HEATING RACK (x2)



Residual temperatures of the heating rack in the top cabinet approximately 302 °F / 150 °C, based on the oven working at 572 °F / 300 °C.